




ARGO-1200-LP

CLEVERTRONICS LP ARGO LED WEATHERPROOF BATTEN
WITH INTEGRAL BATTERY, SWITCHABLE COLOUR & OUTPUT



PRODUCT INFORMATION

Part Number	ARGO-1200-LP
MIC	AUB02320470002
Description	LP Premium ARGO 1200mm LED Weatherproof Emergency Batten with Integral Battery, Switchable Colour and Output, Enabled with Clevertest Plus
Construction	Polycarbonate Base and Diffuser with Captive Stainless-Steel Clips (SS301)
Mounting	Surface mount
Dimensions L x W x H	1265mm x 121mm x 88mm
Weight	2.6 kg
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Polycarbonate
Driver / Ballast	LED Driver – 40w Stallion, SP
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95 @ default
Inrush Current	37A<60μs
Earth Leakage	0.394mA
Supply Current	162mA +/-20mA
Total lumen output	4568lm (128lm/W @4000K, based on non-emergency), details see table Page 2
Power Consumption	see table Page 2
IP Rating	IP65
Operating Temperature	0°C to 40°C
Impact Rating	IK08
AS2293 Classification	C ₀ =D63 C ₉₀ =D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	



ARGO-1200-LP

CLEVERTRONICS LP ARGO LED WEATHERPROOF BATTEN
WITH INTEGRAL BATTERY, SWITCHABLE COLOUR & OUTPUT



REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	Battery
AUM02370050001 CLIFE-PRO-CKIT-NP	Driver
1330083	240V Driver
8002700	LED Strip
8002681 x2	240V LED Strip

Colour	Power Consumption				Standby Lamp OFF	Lumen Output	
	High Output (700mA)		Low Output (350mA)			High Output (700mA)	Low Output (350mA)
	MAX Charge Lamp ON	Standby Lamp ON	MAX Charge Lamp ON	Standby Lamp ON			
3000K	40 W	38 W	22 W	20 W	0.4 W	3819 lm	2260 lm
4000K	38 W	36 W	21 W	19 W	0.4 W	4568 lm	2431 lm
5700K	40 W	38 W	22 W	20 W	0.4 W	4100 lm	2400 lm

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order