




ARGO-1200

CLEVERTRONICS 240V ARGO LED WEATHERPROOF BATTEN
WITH SWITCHABLE COLOUR & OUTPUT



PRODUCT INFORMATION

Part Number	ARGO-1200
MIC	AUB04620360002
Description	240V ARGO 1200mm Weatherproof Batten with Switchable Colour & Output
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless-Steel Clips (SS301)
Mounting	Surface mount
Dimensions L x W x H	1265mm x 121mm x 88mm
Weight	2.3 kg
Diffuser	Polycarbonate
Driver / Ballast	LED Driver - 40W Stallion, SP2, Dip Switch
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], (CRI) Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Supply Current	180mA +/- 20mA
Inrush Current (Max)	15.909A, 160µs
Earth Leakage	0.037-0.047mA
Total lumen output	4608lm (125lm/W) @default (refer to table on next page for details)
Power Consumption	36.8 W @default (refer to table on next page for details)
IP Rating	IP65
Operating Temperature	-25°C to 40°C
Impact Rating	IK08
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	



ARGO-1200

CLEVERTRONICS 240V ARG0 LED WEATHERPROOF BATTEN
WITH SWITCHABLE COLOUR & OUTPUT



REPLACEMENT PARTS

COMPONENT	PART NUMBER & DESCRIPTION
1330098	240V Driver
8002682 x2	240V LED Strip

Power Consumption & Lumen Output	Output 2 (700mA)	
	Lamp On	Lumen Output
3000K	38.6W	4190 lm
4000K (DEFAULT)	36.8W	4608 lm
5700K	38.3W	4350 lm

Power Consumption & Lumen Output	Output 1 (350mA)	
	Lamp On	Lumen Output
3000K	18.2W	2282 lm
4000K	18.7W	2412 lm
5700K	18.6W	2355 lm

*The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order