



ARGOPRO-1200-SEN-L10POD-HV

CLEVERTRONICS Argonaut Pro 1200mm Weatherproof Emergency Batten, L10 with POD, Motion Sensor, Zoneworks Hive



| PRODUCT INFORMATION | |
|--------------------------|---|
| Product Code | ARGOPRO-1200-SEN-L10POD-HV |
| MIC | AUB01820460001 |
| Description | Argonaut Pro 1200mm Weatherproof Emergency Batten, L10 with POD, Motion Sensor, Zoneworks Hive |
| Colour CCT | 4000K |
| Output Configuration | Configurable Quad Output |
| Battery Configuration | Batteries contained within thermally isolated POD for optimum battery life |
| Construction | Polycarbonate Base and Diffuser w/Stainless Steel Clips (SS316) |
| Diffuser | Polycarbonate |
| Mounting | Surface Mount |
| Operating Mode | SUSTAINED |
| Testing System | Zoneworks XTHIVE (RF) |
| Battery | Lithium Nanophosphate, 3.3V 5000mAh |
| Charging Method | Intelligent current limited constant voltage |
| Sensor Capability | High/Low, On/Off, Master Slave - Yes |
| Dimensions LxWxH (mm) | 1330x160x105 |
| Weight (kg) | 3.2 |
| Driver / Ballast | LED Driver - TCI DC MAXI JOLLY SVM 65 DALI SLIM |
| Lamp(s)* | LED strip module, 4000K, Ra>80 L70/B50 Ta 40°C; LM80 Report >60,000hr, Projected 184,000hr L80/B20 Ta 40°C; LM80 Report >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; LM80 Report 43,000hr, Projected 43,000hr |
| Supply Voltage | 220-240V~ 50Hz |
| Power Factor | 0.92 @ default |
| Supply Current | 221mA +/-20mA |
| Inrush Current (Max) | 17.8A<1300µs |
| Earth Leakage | 0.42mA |
| Total Lumen Output | 4660 lm (148 lm/W) @ default (refer to next page for details) |
| Power Consumption | 31.6W @ default (refer to next page for details) |
| Operating Temperature | 0°C to 40°C |
| IP Rating | IP65 |
| Impact Rating | IK08 |
| LED MacAdam Step (SDCM) | 3 |
| AS2293 Classification | C0=D80 C90=D80 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |



ARGOPRO-1200-SEN-L10POD-HV

CLEVERTRONICS Argonaut Pro 1200mm Weatherproof Emergency Batten, L10 with POD, Motion Sensor, Zoneworks Hive



REPLACEMENT PARTS

| COMPONENT | PART NUMBER & DESCRIPTION |
|------------------|---|
| 240V Driver | 1330151 - LED Driver - TCI DC MAXI JOLLY SVM 65 DALI SLIM |
| 240V LED Strip | 8002755 - PCA:LED Strip ARGOPRO-1200,HT10540-A1,16P16S,4000K |
| Emergency Driver | AUM01870090001 - Lifelight Pro,Control Only, L10, HV, OWC, NP |
| EM LED Strip | 8050205 - HWSUB: CT10570-A4 - 2 LED WHITE |
| Battery | 1530050 - BATTERY:L10 3.3V 2.5AH 70mm lead, no Brkt |
| Sensor | 1190118 - SENSOR: Microwave Motion, IP20, MC049V |

| Power Consumption & Lumen Output | Max Charge, Lamp On | Standby Charge, Lamp On | Standby Charge, Lamp Min. 10% (sensor version only) | Standby Charge, Lamp Off | Lumen Output |
|----------------------------------|---------------------|-------------------------|---|--------------------------|--------------|
| Output 4 (900mA) | 45.7W | 43.4W | 6.0W | 0.7W | 6259 lm |
| Output 3 (750mA) | 39.3W | 37.0W | 5.5W | 0.7W | 5495 lm |
| Output 2 (650mA) DEFAULT | 33.9W | 31.6W | 4.7W | 0.7W | 4660 lm |
| Output 1 (500mA) | 27.1W | 24.8W | 6.2W | 0.7W | 3541 lm |

*The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order