



ARGOSQ-SEN

CLEVERTRONICS ARGONAUT SQUARE
WEATHERPROOF NON-EMERGENCY LIGHT WITH MOTION SENSOR (HI/LO)



PRODUCT INFORMATION

Part Number	ARGOSQ-SEN
MIC	INS04620030001
Description	Argonaut Square Weatherproof Non-Emergency Light with Motion Sensor (Hi/Lo)
Output Configuration	Fixed Single Output
Construction	Die-cast Aluminium Body with Polycarbonate Diffuser
Mounting	Surface mount
Sensor Capability	High/Low, On/Off, Master Slave Capable - No
Dimensions L x W x H	321mm x 321mm x 97mm
Weight	3.0kg
Diffuser	Polycarbonate
Driver / Ballast	Clevertronics Stallion 40W
Lamp(s)	LED module, 4000K cool white, Ra>80 L70/B50 Ta 40°C; Reported >60,000hr, Projected 205,000hr L80/B20 Ta 40°C; Reported >60,000hr, Projected 100,000hr L90/B10 Ta 40°C; Reported >43,000hr, Projected 43,000hr
Supply Voltage	220-240V~ 50Hz
Power Factor	0.91
Supply Current	100mA +/- 20mA
Inrush Current (max)	36.8A<100µs
Earth Leakage	0.33mA
Total Lumen Output	3242lm @ 149.8lm/W
Power Consumption	21.6W (Lamp ON), 3.1W (Lamp ON Min 10%)
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	N/A
Applicable Standards ANZ	AS/NZS3820, CISPR15, AS/NZS60598.1, EN 60598-2-1, BS EN IEC 55015, BS EN 61547, BS EN IEC 61000-3-2
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
8050780	LED Panel: HWSUB: CT10746-D2
1330095	LED Driver - 40W Stallion, MS-HL2, 470mA
1190133	SENSOR: Head Only, t/s MLC65-P8, GM2 Mods

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.