



## CBKLEDN-DALI-SLV

CLEVERTRONICS LP LED WEATHERPROOF BUNKALITE, SILVER



### PRODUCT INFORMATION

|                             |  |
|-----------------------------|--|
| Part Number                 | CBKLEDN-DALI-SLV   |
| MIC                         | AUS02220240002   |
| Description                 | LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire, Silver body, DALI Registered |
| Construction                | Base Material: Die-cast aluminium<br>Diffuser Cover Material: Opal Polycarbonate         |
| Mounting                    | Surface Mount  |
| Dimensions L x W x H        | 360mm (Diameter), 145mm (Height)   |
| Weight                      | 4.5kg  |
| Operating Mode              | Non-Maintained Operation   |
| Testing System              | DALI Registered  |
| Battery Type & Manufacturer | Lithium Iron Phosphate (LiFePO4), Clevertronics  |
| Charging Method             | Intelligent Current Limited Constant Voltage   |
| Driver                      | Constant current, 650mA (Emergency)  |
| Lamp(s)                     | LED module, 4,000K natural white, 50,000h life (L70/B50), Ra>80                          |
| Operating Voltage           | 220-240V~ 50Hz   |
| Total Lumen Output          | 237lm (Emergency)  |
| Power Consumption           | 1.0 Watts (Standby), 4.2 Watts (Max)   |
| Rated Emergency Duration    | 120 Minutes  |
| IP Rating                   | IP65   |
| IK Rating                   | IK10   |
| Operating temperature       | 0°C to 40°C  |
| AS2293 Classification       | C0=D32, C90=D32  |
| Applicable Standards        | AS/NZS3820, CISPR15, AS/NZS60598.1   |
| Compliance Marking (RCM)    |  |

### REPLACEMENT PARTS

| PART NUMBER                          | DESCRIPTION |
|--------------------------------------|-------------|
| 1550010                              | Battery     |
| CLIFE-CKIT-DALI-NP<br>AUM02270170002 | Driver Pack |
| 8011801                              | LED Strip   |
| 8003060                              | DALI Node   |