



## CBKLEDN-DALI-WHT

CLEVERTRONICS LP LED WEATHERPROOF BUNKALITE, WHITE



| PRODUCT INFORMATION         |   |
|-----------------------------|---|
| Part Number                 | CBKLEDN-DALI-WHT  |
| MIC                         | AUS02220030102  |
| Description                 | LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire, White body, DALI Registered |
| Construction                | Base Material: Die-cast aluminium<br>Diffuser Cover Material: Opal Polycarbonate        |
| Mounting                    | Surface Mount   |
| Dimensions L x W x H        | 360mm (Diameter), 145mm (Height)  |
| Weight                      | 4.5kg   |
| Operating Mode              | Non-Maintained Operation  |
| Testing System              | DALI Registered   |
| Battery Type & Manufacturer | Lithium Iron Phosphate (LiFePO4), Clevertronics   |
| Charging Method             | Intelligent Current Limited Constant Voltage  |
| Driver                      | Constant current, 650mA (Emergency)   |
| Lamp(s)                     | LED module, 4,000K natural white, 50,000h life (L70/B50), Ra>80                         |
| Operating Voltage           | 220-240V~ 50Hz  |
| Total Lumen Output          | 237lm (Emergency)   |
| Power Consumption           | 1.0 Watts (Standby), 4.2 Watts (Max)  |
| Rated Emergency Duration    | 120 Minutes   |
| IP Rating                   | IP65  |
| IK Rating                   | IK10  |
| Operating temperature       | 0°C to 40°C   |
| AS2293 Classification       | C0=D32, C90=D32   |
| Applicable Standards        | AS/NZS3820, CISPR15, AS/NZS60598.1  |
| Compliance Marking (RCM)    |   |

| REPLACEMENT PARTS                    |             |
|--------------------------------------|-------------|
| PART NUMBER                          | DESCRIPTION |
| 1550010                              | Battery     |
| CLIFE-CKIT-DALI-NP<br>AUM02270170002 | Driver Pack |
| 8011801                              | LED Strip   |
| 8003060                              | DALI Node   |