

CBKLEDS-HV-GRY

LP LED Weatherproof Bunkalite - Grey



PRODUCT INFORMATION	
Part Number	CBKLEDS-HV-GRY
MIC	AUS02820320002
Description	LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire, Grey
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver	Constant current, 480mA, 50,000hrs
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Supply Current	0.071A
Power Factor	0.93
Total Lumen Output	1976lm @ 130lm/W (based on non-emergency version)
Power Consumption	18.4 Watts (MAX Lamps ON), 1.3 Watts (Standby Lamp OFF)
Inrush Current (Max)	10.226A, 106µs
Earth Leakage	OA .
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	<u>&</u>

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550010	Battery
1331102-B	LED Driver
8011800	LED Strip
AUM02870580001 CLIFE-CKIT-HVEXTA-NP-220	Driver Pack
8003195	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

