

CLEVERTRONICS LP LED WEATHERPROOF BUNKALITE, WHITE (ZONWORKS XTHIVE)



PRODUCT INFORMATION

Catalogue Number	CBKLEDS-WW-HV-WHT
MIC	AUC02810010001
Description	LP Premium Bunkalite IP65 Weatherproof Emergency Luminaire, Warm White, White Body
Construction	Base Material: Die-cast aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions L x W x H	Diameter 360mm, Depth 145mm
Weight	4.5kg
Operating Mode	Sustained
Testing System	Zoneworks XTHIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Polycarbonate
Driver / Ballast	Constant current, 500mA, 50,000hrs
Lamp(s)	LED module, 3,000K Warm White, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Total lumen output	1350 lm @ 75lm/W (84lm/W non-emergency version)
Power Consumption	18 Watts (Lamps ON), 1.7 Watts (Lamp OFF)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D20 C ₉₀ =D20
Impact Rating	IK10

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550010	BATT:LP 3.2V 3200mAh 200mm lead,BRKT.
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug
1330050	LED Driver - 20w 350-700mA
8003190	PCA: RF Node CT10678-Ax internal antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order