



CLEVERTRONICS LP LED TUBE WIRE GUARD BATTEN



PRODUCT INFORMATION

Catalogue Number	CBS2L2S-LT-WG-MS
Description	LP Premium 2 x LED tube 2ft Wire Guard Batten with LED Emergency POD and Microwave Sensor Control of the Lamps (on/off) Enabled with Clevertest Plus
Construction	Powder coated Steel body with PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	666mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Wire Guard
Lamp(s)	2x Philips CorePro LEDtube T8, Col. 840, 30,000hours
Operating Voltage	240V AC; 50Hz
Total lumen output	1430 lm @ 89lm/W (based on non-EM version)
Power Consumption	17 Watts (Lamp ON), 1.0 Watts (Standby Lamp OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT
3170030	LED TUBE 8W/840, 0.6m
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug
1190116	SENSOR: Microwave Motion, IP20, HC009S