



CBS2L4S-LT-WG-HV

CLEVERTRONICS LP LED TUBE WIREGUARD BATTEN
(ZONWORKS XT HIVE)



PRODUCT INFORMATION

Part Number	CBS2L4S-LT-WG-HV
MIC	AUB02810090001
Description	LP Premium LED Tube, Wire Guard Batten with LED Emergency POD
Construction	Powder Coated Steel Body with PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	1271mm x 120mm x 108mm
Weight	3.9kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Wire Guard
Lamp(s)	2 x 1200mm OZON LED Tube 18W840, 50,000 Hours
Operating Voltage	240V AC; 50Hz
Total lumen output	3735 lm @ 106 lm/W
Power Consumption	40W (MAX charging, Lamp ON), 37W (Standby, Lamp ON), 1W (Standby, Lamp OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	BATT:LiFePO4 3.2V 3.2Ah 70mm lead,noBRKT
3170081	Ozon LED TUBE 18W/840, 1.2m (x2)
AUM02870100001 CLIFE-CKIT-HVEXTA-NP	Lifelight, Control Only, HV, LP, No Plug (incl. Hive node)
8003194	PCA: RF Node CT10678-A7 Ext Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order