



## CBS2L4S-LT-WG-MS-DALI

CLEVERTRONICS LP LED TUBE WIREGUARD BATTEN  
(DALI)



### PRODUCT INFORMATION

Part Number	CBS2L4S-LT-WG-MS-DALI
MIC	AUB02210940002
Description	LP Premium 2 x LED tube 2ft Wire Guard Batten with LED Emergency POD and Microwave Sensor Control of the Lamps (on/off)
Construction	Powder coated Steel body with PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	666mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Wire Guard
Lamp(s)	2x Philips CorePro LEDtube T8, Col. 840, 30,000hours
Operating Voltage	240V AC; 50Hz
Power Consumption	17 Watts (Lamp ON), 1.0 Watts (Standby Lamp OFF)
Total Lumen Output	1430 lm @ 89lm/W (based on non-EM version)
Operating Temperature	1°C to 40°C
IP Rating	IP20
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
3170081	LED Tube
8050215	Emergency LED
AUM02270170002 CLIFE-CKIT-DALI-NP	Driver Pack
1190116	Microwave Sensor
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.