

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN (DALI)



PRODUCT INFORMATION

Catalogue Number	CBS2LEDS-DIF-DD-DALI
MIC	AUB02211020001
Description	LP Premium Quantum LED Diffused Batten with Dali Driver and LED Emergency Pod
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	630mm x 120mm x 110mm
Weight	2.0kg
Operating Mode	Sustained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver	LED DALI Driver - 25W, 350-1050mA, 20-50V, one4all
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	2187lm @ 99 lm/W (non-emergency mode)
Power Consumption	24W (Max charging, Lamp ON), 22W (Standby, Lamp ON), 0.4W (Standby, Lamp OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330038	LED DALI Driver - 25W, 350-1050mA, 20-50V, one4all
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug
8003060	PCA: DALI Node #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order