

CBS2LEDS-DIF-DD-HV

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN (ZONEWORKS XT HIVE)



PRODUCT INFORMATION	
Part Number	CBS2LEDS-DIF-DD-HV
MIC	AUB02810010001
Description	LP Premium Quantum LED Diffused Batten with Dali Driver and LED Emergency Pod, Zoneworks XT Hive (RF)
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface mount
Dimensions L x W x H	630mm x 120mm x 110mm
Weight	2.0kg
Operating Mode	Sustained
Testing System	Zoneworks XT Hive (RF)
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	LED DALI Driver
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	1.3 Watts (Standby) 25.9 Watts (Max)
Total Lumen Output	2187lm @102lm/W (non-emergency mode)
Operating Temperature	1°C to 40°C
IP Rating	IP20
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	&

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550050	Battery
1100635	LED Strip
1330038	240V Driver
AUM02870100001 CLIFE-CKIT-HVEXTA-NP	Driver Pack
8003191	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

