



CBS2LEDS-DIF-MS-DALI

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN,
MICROWAVE SENSOR (DALI)



PRODUCT INFORMATION

Part Number	CBS2LEDS-DIF-MS-DALI
MIC	AUB02211080002
Description	LP Premium Quantum LED diffused batten with LED Emergency Pod and microwave sensor control of the lamps (on/off)
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	664mm x 120mm x 108mm
Weight	2.0kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	Driver: 40w, 500-1050mA, 15-50V
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	1.8W (Standby), 27.1W (MAX)
Total Lumen Output	2187lm @102lm/W
Operating Temperature	1°C to 40°C
IP Rating	IP20
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery
1100635	LED Strip
1330029	240V Driver
1190117	Microwave Sensor
AUM02270170002 CLIFE-CKIT-DALI-NP	Driver Pack
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.