

CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN (ZONWORKS XT HIVE)



PRODUCT INFORMATION

Catalogue Number	CBS4LEDS-DIF-DD-HV
MIC	AUB02810170001
Description	LP Premium Odyssey Quantum LED Diffused Batten with LED Emergency Pod and Dali Driver
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface Mount
Dimensions L x W x H	1271mm x 120mm x 108mm
Weight	3.3kg
Operating Mode	Sustained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver	DALI Driver: 50W 350-1050mA
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	220-240V AC; 50Hz
Power Factor	0.95
Total lumen output	4585lm @ 118lm /W
Power Consumption	44W (Max charging, Lamp ON), 40W (Standby, Lamp ON), 1.3W (Standby, Lamp OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330056	LED Driver - LCA 50w 350-1050mA,ONEFORALL
AUM02870160001 CLIFE-CKIT-HV-NP	Lifelight, Control Only, HV, LP, OWC, 650mA (incl. HIVE Node)
8003190	RF Node CT10678-Ax Internal Antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order