

## CLEVERTRONICS LP ODYSSEY QUANTUM LED DIFFUSED BATTEN & MICROWAVE SENSOR



### PRODUCT INFORMATION

Part Number	CBS4LEDS-DIF-MS-HL
MIC	AUB02310080001
Description	LP Premium Quantum LED diffused batten with LED Emergency Pod and Hi/Lo Microwave Sensor Control of the Lamps (10%-100%)
Construction	Powder coated steel body with acrylic prismatic diffuser and PC/ABS end caps
Mounting	Surface mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Prismatic
Driver / Ballast	Hytronik HED1050H/C
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Total lumen output	4585lm @ 109lm/W (112lm/W for non-EM version)
Power Consumption	42 Watts (Standby lamps max), 8.6 Watts (Standby lamps min)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
8002695	PCA:LED Strip 8S6P, ALS-13-840-0-02-B
1330070	LED Driver - HED1050H/C, 50w
1190127	SENSOR:HC403V-KD w SAM4, 650mm cable
CLIFE-CKIT-NP	Lifelight, Control Only, LP, No Plug

