

## CLEVERTRONICS LP 1200MM (4ft) NON-MAINTAINED BARE BATTEN REPLACEMENT



### PRODUCT INFORMATION

Catalogue Number	CBS4N-DALI
Description	LP 1200mm (4ft) non-maintained bare batten replacement utilising the Lifelight PRO - High Performance, Emergency Light with Lithium Battery Technology
Mounting	Surface Mount
Dimensions L x W x H	1220mm x 110mm x 50mm
Operating Mode	Non-Maintained
Testing System	DALI Registered
Ballast	N/A
Charging Method	Intelligent current limited constant voltage charger
Lamps(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V 50Hz
Power Consumption	0.4 Watts (standby)
IP Rating	IP20
Impact Rating	N/A
Operating Temperature	1° to 40°C (Ambient)
AS/NZ2293 Classification	C <sub>0</sub> =D63 C <sub>90</sub> =D63

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1100830	2 x 3W LED Round Head Assembly – White
1550230	Battery, LP 3.2V 6400mAh.200mm lead.Brkt.
CLIFE-PRO-CKIT	Lifelight Pro, Control Gear Only, LP Lithium
8003060	PCA: New DALI 3CT10629-Ax

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*