



CBS4N

CLEVERTRONICS LP 1200MM NON-MAINTAINED BATTEN REPLACEMENT



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | CBS4N |
| MIC | AUB02310140003 |
| Description | LP Premium 1200mm Non-Maintained Bare Batten Replacement utilising the Lifelight PRO, Enabled with Clevertest Plus |
| Construction | Powder coated Steel Body and ABS/Polycarbonate End Caps |
| Mounting | Surface Mount |
| Dimensions L x W x H | 1220mm x 110mm x 50mm |
| Operating Mode | Non-maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Iron Phosphate, 3.2V 6400mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 0.4 Watts (Standby), 2.7Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =D80 C ₉₀ =D80 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------------------------------|--|
| 1550230 | BATTERY:LP 3.2V 6400mAh 200mm lead.Brkt. |
| 1100866 | LED: Lifelight Pro Head Assem,Ld:500mm,Round,Gen 2, LT |
| AUM02370050001 CLIFE-PRO-CKIT-NP | Lifelight Pro, Control Only, 530mm, NP, CTP, OWC |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.