



CCFLED-DALI-BLK

CLEVERTRONICS LP CLEVERFIT EXIT, BLACK



PRODUCT INFORMATION	
Part Number	CCFLED-DALI-BLK
MIC	AUA02210030003
Description	LP Premium Cleverfit Emergency Exit, Black
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 4.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E2.5 C ₉₀ =E2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550105	Battery
8002329	Driver
8002710	LED Strip
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order