



CCFLED-DALI

CLEVERTRONICS LP CLEVERFIT EXIT



PRODUCT INFORMATION	
Part Number	CCFLED-DALI
MIC	AUA02210010002
Description	LP Premium Cleverfit Emergency Exit
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 1500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	3.3 Watts (Standby), 4.2 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E2.5 C ₉₀ =E2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550190	BATT: LP 3.2V 1500mAh 390mm lead, no BRKT
8002328	DRIVER: PCA:CCFLED Driver CT10164-L6 6C50 Dali Reg HV
8002120	LED: PCA:DLED Cleverfit LightStrip,CT10152-D2
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order