



CCFPRO-TH-HV-DS-RAOW

CLEVERTRONICS LP CLEVERFIT PRO EXIT – THEATRE MASK



PRODUCT INFORMATION	
Part Number	CCFPRO-TH-HV-DS-RAOW
MIC	AUA02860260001
Description	LP Premium Cleverfit Pro Emergency Exit, Theatre Mask
Construction	Fire-retardant PC/ABS body with Polycarbonate Diffuser
Mounting	Wall, Ceiling Double-Sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.5kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask, Running Man Arrow One Way
Lamp(s)	6 x Duris LED, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.5 Watts (Standby), 3.4 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550105	Battery
8003156	Driver
8002710	Emergency LED Panel
8003191	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order