

CGEKED-80-WM-DALI-RL

CLEVERTRONICS LP GIGANTOR EXIT



PRODUCT INFORMATION	
Part Number	CGELED-80-WM-DALI-RL
MIC	AUA02210840002
Description	LP Premium Wall Mount Gigantor Exit, 80 metre viewing Distance
Construction	Powder coated Metal Frame with Acrylic Diffuser
Mounting	Wall Mount, Single-Sided
Dimensions L x W x H	1305mm x 170mm x 560mm
Weight	21kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 6400mAh Lithium Iron Phosphate, 6.4V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Running Man Left (must specify diffuser combination)
Lamp(s)	LED strip module, 4,000K natural white, 50,000h life [L70/B50 Ta 40°C], Ra>80 2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	23.6 Watts (Standby), 30.6 Watts (Max)
Operating Temperature	1°C to 40°C
IP Rating	IP20
Distance	80m
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	&

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550290	Battery for Emergency Exit Driver
1550230	Battery for Emergency Escape Driver
AUM02270030102	Emergency Exit Driver
CCPLED-38V120C-CKIT-DALI	
AUM02270220002 CLIFE-PRO-CKIT-DALI-NP	Emergency Escape Driver
1330054	240V LED Driver – Exit Sign
1100830	LED Head Assembly
8003060	DALI Node for Emergency Exit Driver
8003065	DALI Node for Emergency Escape Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

