



## CGELED-80-WM-RR

### CLEVERTRONICS LP WALL MOUNT GIGANTOR EXIT



PRODUCT INFORMATION	
Part Number	CGELED-80-WM-RR
MIC	AUA02310260001
Description	LP Premium Wall Mount Gigantor Exit, 80 metre Viewing Distance, Enabled with Clevertest Plus
Construction	Powder coated Metal Frame with Acrylic Diffuser
Mounting	Wall Mount, Single-Sided
Dimensions L x W x H	1305mm x 170mm x 560mm
Weight	21kg
Operating Mode	Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 1 x 3.2V 6400mAh (Exit), 1 x 6.4V 3200mAh (EM)
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Running Man, Arrow Right (must specify diffuser combination)
Lamp(s)	Exit: LED strip module, 4,000K natural white, Ra>80, LED Lifetime: >100,000hrs (AS/NZS2293.3 LSL=39Y/00M), Ta 40°C EM: 2 x 3W LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	23 Watts (Standby), 30 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Viewing Distance	80m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550290	BATT:LP 6.4V 3.2Ah.200mm lead.Stick.Brkt
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
1330054	LED Driver - LC 38w 500-700mA, 20-54V
8002690	PCA:LED Strip Argonaut Stand & tray,1.2m
1100869	Lifelight Pro Head Assembly, Ld:280mm,Rnd,LT,Gen 2
AUM02370180001 CCPLED-38V120C-CKIT	LED Power Pack, 38V 120mA, LP, CTP
AUM02370050001 CLIFE-PRO-CKIT-NP	Lifelight Pro, Control Only, 530mm, NP, CTP, OWC

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order