



CLIFE-2PRO-SMS-1200

CLEVERTRONICS LP LIFELIGHT PRO SURFACE MOUNT



PRODUCT INFORMATION

Part Number	CLIFE-2PRO-SMS-1200
MIC	AUT02310030004
Description	LP Premium LifeLight PRO, high performance, surface mount twin Emergency Light, Enabled with Clevertest Plus
Construction	Powder coated metal enclosure
Mounting	Surface mount and can also be chain suspended
Dimensions L x W x H	1220mm x 110mm x 50mm
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 5.4 Watts (Max)
Operating Temperature	1°C to 40°C
IP Rating	IP20
AS2293 Classification	C ₀ =D160 C ₉₀ =D160
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
CLIFE-PRO-CKIT-NP AUM02370050001	LifelightPro,Control Only,Batten,LP, NP
1100866	Lifelight Pro Head Assem,Ld:500mm,Round,Gen 2, LT

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.