



CLIFE-2PRO-SMS-DALI-1200-BLK

CLEVERTRONICS LP LIFELIGHT PRO SURFACE MOUNT TWIN EMERGENCY, BLACK



PRODUCT INFORMATION	
Part Number	CLIFE-2PRO-SMS-DALI-1200-BLK
MIC	AUT02210380002
Description	LP Premium LifeLight PRO, High Performance, Surface Mount Twin Emergency Light, Black
Construction	Powder Coated Metal Enclosure PC/ABS Heads
Mounting	Surface Mount, can also be Chain Suspended
Dimensions L x W x H	1220mm x 110mm x 50mm
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Twin Dual LED (Lifetime Warranty on the Lamp Head and Loom Assembly)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.4W (Standby), 6.0W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D160 C ₉₀ =D160
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550230	Battery
1100872	LED Head Assembly
AUM02270220002 CLIFE-PRO-CKIT-DALI-NP	Driver Pack
8003060	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.