

CLEVERTRONICS LP LIFELIGHT PRO SURFACE MOUNT



PRODUCT INFORMATION

Part Number	CLIFE-2PRO-SMS-DALI-1200
MIC	AUT02210030102
Description	LP Premium LifeLight PRO, high performance, surface mount twin Emergency Light
Construction	Powder coated metal enclosure
Mounting	Surface mount and can also be chain suspended
Dimensions L x W x H	1220mm x 110mm x 50mm
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 4.4 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D125 C ₉₀ =D125

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
CLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,LP, NP
1100830	Lifelight Pro Head Assembly, Round
8003060	PCA: DALI Node #CT10629-Ax

