



## CLIFE-2PRO-SMS-HV-1200

CLEVERTRONICS LP LIFELIGHT PRO SURFACE MOUNT



PRODUCT INFORMATION	
Part Number	CLIFE-2PRO-SMS-HV-1200
MIC	AUT02810140001
Description	LP Premium LifeLight PRO, High Performance, Twin Emergency Light
Construction	Powder coated metal enclosure
Mounting	Surface Mount, can also be chain suspended
Dimensions L x W x H	1220mm x 110mm x 50mm
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 4.4 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D160 C90=D160
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt. (QTY 2)
8003081	LED:PCA: LLPRO HEAD Alum #CT10640-D4 - GW CSHPM 'LT' (QTY 2)
AUM02870230001 CLIFE-PRO-CKIT-HVEXTA-NP	Lifelight Pro, Control Only, HVEXTA, LP (QTY 2) (incl. HV node)
8003194	PCA: RF Node CT10678-A12 Ext Antenna LLPro (QTY 2)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.