



CLIFE-PRO-DALI

CLEVERTRONICS LP LIFELIGHT PRO



PRODUCT INFORMATION

Part Number	CLIFE-PRO-DALI
MIC	AUT02210060004
Description	LP Premium LifeLight PRO, high performance, recessed Emergency Light
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm head diameter (95mm with adaptor plate)
Cut-Out	51mm (85mm with adaptor plate)
Minimum Depth	200mm (120mm with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz (supplied with a 2 core and earth flex and plug)
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
AUM02270190002 CLIFE-PRO-CKIT-DALI	Lifelight Pro, Control Only, Batten, Dali Reg, LP (incl. DALI node)
1100868	Lifelight Pro Head Assbly,Rnd,Large+Ring, LT,Gen 2
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.