



CLIFE-PRO-HV-RECWP-WHT

CLEVERTRONICS LP LIFELIGHT PRO RECESSED IP65 WEATHERPROOF LED EMERGENCY LUMINAIRE (ZONENETWORKS XT HIVE)



PRODUCT INFORMATION

Part Number	CLIFE-PRO-HV-RECWP-WHT
MIC	AUT02820040001
Description	LP LifeLight PRO Recessed IP65 Weatherproof LED Emergency Luminaire
Construction	Die Cast Aluminium Body 316 Stainless Steel Screws Clear Toughened Glass
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm (head diameter)
Cut-Out	106mm
Minimum Depth	120mm
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP65 (Lamp head only)
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
AUM02870070001 CLIFE-PRO-CKIT-HV	Lifelight Pro, Control Only, LP, HV
1100817	Lifelight Pro Head Assembly, Round, LT, Gen 2, Blk
8003191	PCA: RF Node CT10678-A9 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.