



# CLIFE-PRO-HV-SPOT-BLK

## CLEVERTRONICS LP LIFELIGHT PRO SPOTLIGHT EMERGENCY



PRODUCT INFORMATION	
Part Number	CLIFE-PRO-HV-SPOT-BLK
MIC	AUT02810250001
Description	Lifelight PRO, High Performance, Recessed Emergency Spotlight, Black
Construction	Lamp head assembly with adjustable lamp head direction Control gear and battery – Remote mounted and connected via the standard 1m length of cable (same as the standard Lifelight PRO)
Mounting	Ceiling or wall mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack), 105mm x 100mm x 60mm (Lamp Head and Swivel)
Operating Mode	Non-Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate 3.2V 6.4Ah 20.5Wh
Charging Method	Intelligent current limited constant voltage charger
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V 50Hz
Power Consumption	0.7 Watts (Standby), 5.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C (Ambient)
AS2293 Classification	N/A (C0=D80, C90=D80 if/when the LED head is facing the floor)
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
1100843	Lifelight Pro Head Assembly, Round, Blk, Gen 2
AUM02870070001 CLIFE-PRO-CKIT-HV	Lifelight Pro, Control Only, LP, HV (incl. Hive node)
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.