



CLIFE-PRO-RECWP-BLK

CLEVERTRONICS LP LIFELIGHT PRO IP65 WEATHERPROOF EMERGENCY - BLACK



PRODUCT INFORMATION	
Part Number	CLIFE-PRO-RECWP-BLK
MIC	AUT02320110001
Description	LP Premium LifeLight PRO, High Performance, IP65 recessed Emergency Light with Remote Gear (IP20), Enabled with Clevertest Plus, Black
Construction	Die Cast Aluminium Body, 316 Stainless Steel Screws, Clear Toughened Glass
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm head diameter
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4W (Standby), 2.7W (Max)
IP Rating	IP65 (Lamp head only)
IK Rating	IK10
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550230	BATT:LP 3.2V 6400mAh.200mm lead.Brkt.
AUM02370100001 CLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP, OWC Lifelight Pro, Control Only, LP, OWC
1100817	Lifelight Pro Head Assembly, Round, LT, Blk, Gen 2

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.