

## CLEVERTRONICS LP LIFELIGHT PRO IP65 WEATHERPROOF SURFACE MOUNT EMERGENCY (DALI)



### PRODUCT INFORMATION

Catalogue Number	CLIFE-PRO-SM-WP-DALI
MIC	AUT02220060001
Description	LP Premium Lifelight PRO, High Performance, Weatherproof, Surface Mounted Emergency Light
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max)
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
AS2293 Classification	C <sub>0</sub> =D80 C <sub>90</sub> =D80

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550231	BATT:LP 3.2V 6400mAh.200mm lead, No Brkt
8050170	LED: HWSUB: CT10668-D1
8002924	Driver: PCA: xLIFEPro SM #CT10142-L9 2C250/550 CTP AU

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*