



CUBPRO-TH-DALI-DS-RAOW

CLEVERTRONICS LP ULTRABLADE PRO, THEATRE



PRODUCT INFORMATION

| | |
|--------------------------|--|
| Part Number | CUBPRO-TH-DALI-DS-RAOW |
| MIC | AUA02260530002 |
| Description | LP Premium Ultrablade Pro blade Exit, Theatre |
| Construction | PC/ABS body with PC diffuser |
| Mounting | Recessed ceiling |
| Dimensions L x W x H | 317mm x 157mm x 8.7mm (Blade Assembly) 385mm x 67mm (Cover Plate) |
| Cut-Out | 350mm x 48mm |
| Minimum Depth | 80mm |
| Weight | 1.1kg |
| Operating Mode | Maintained |
| Testing System | DALI Registered |
| Battery | Lithium Iron Phosphate, 3.2V 1500mAh |
| Charging Method | Intelligent current limited constant voltage |
| Diffuser | Theatre mask, Running Man Arrow One Way, Double Sided |
| Lamp(s) | 12 x Duris E3 LED, 100,000 hours |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 2.8 Watts (Standby), 4.2 Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| Viewing Distance | 24m |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|------------------------------------|-----------------------|
| 1550105 | Battery |
| 8002178 | Emergency LED Panel |
| AUM02270280002 CUBPRO-CKIT-DALI | Emergency Driver Pack |
| 8003060 | Emergency Node - DALI |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.