



CWELED-TH-DALI-DS-RAOW

CLEVERTRONICS LP WEATHERPROOF EXIT, THEATRE
(DALI REGISTERED)



PRODUCT INFORMATION

Part Number	CWELED-TH-DALI-DS-RAOW
MIC	AUA02260500002
Description	LP Premium Weatherproof Exit, Theatre, DALI Registered
Construction	Polycarbonate Clear Cover, Glass Reinforced Nylon PA66 Base
Mounting	Wall, Ceiling Single-sided & Ceiling Double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask, Running Man Arrow One Way
Lamp(s)	6 x LED 100,000 Hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.8W (Standby), 4W (Max)
IP Rating	IP66/67
Operating Temperature	0°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002710	LED Panel
8002329	Emergency Driver
8003060	Node - DALI

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.