



CWELED-TH-HV-RR

CLEVERTRONICS LP WEATHERPROOF EXIT, THEATRE
(ZONWORKS XT HIVE)



PRODUCT INFORMATION

Part Number	CWELED-TH-HV-RR
MIC	AUA02860240001
Description	LP Premium Weatherproof Exit, Theatre, Zoneworks XT Hive
Construction	Polycarbonate Clear Cover, Glass Reinforced Nylon PA66 Base
Mounting	Wall, Ceiling Single-sided & Ceiling Double-sided
Dimensions L x W x H	410mm x 272mm x 100mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Zoneworks XT Hive (RF)
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Theatre Mask, Running Man Arrow Right
Lamp(s)	6 x LED 100,000 Hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.8W (Standby), 4W (Max)
Inrush current (Max)	12.537A
Earth Leakage	0.31mA
IP Rating	IP66/IP67
Operating Temperature	0°C to 40°C
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550105	Battery
8002710	LED Panel
8002348	Emergency Driver
8003191	Node – HIVE (RF)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.