



## CWFLED-DALI-BLK

CLEVERTRONICS LP LED WEATHERPROOF SUPALITE



### PRODUCT INFORMATION

Part Number	CWFLED-DALI-BLK
MIC	AUE02220030102
Description	LP Premium LED Weatherproof Supalite flood unit, surface mounted Emergency Light, Black
Construction	Polycarbonate
Mounting	Surface wall mount (hard wired supply connection)
Dimensions L x W x H	Main enclosure - 380mm x 190mm x 130mm Total height including LED Heads 310mm
Weight	3.6kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Iron Phosphate, 6.4V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED Heads (adjustable), 600lm per lamp head
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 5.4 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550290	BATT:LP 6.4V 3.2Ah.200mm lead.Stick.Brkt
CCPLED-WP-18V625C-CKIT-DALI AUM02270050102	LED Power Pack,18V 625mA, IP Loom, Dali Reg, LP
1100551	WP Led Head, c/w Led's & Loom
8003065	PCA: New DALI #CT10629-Ax Horizontal

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.