

CLEVERTRONICS LP LED WEATHERPROOF SUPALITE, BLACK (ZONWORKS XT HIVE)



PRODUCT INFORMATION

Catalogue Number	CWFLED-HV-BLK
MIC	AUE02820030001
Description	LP Premium LED Weatherproof Supalite Flood Emergency Light, Black
Construction	Polycarbonate
Mounting	Surface Wall Mount (hard wired supply connection)
Dimensions L x W x H	Main enclosure - 380mm x 190mm x 130mm Total height including LED Heads 310mm.
Weight	3.6kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 6.4V 3200mAh (x2)
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED Heads (adjustable), 600lm per lamp head
Operating Voltage	240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 5.4 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =N/A C ₉₀ =N/A

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550290	BATT:LP 6.4V 3.2Ah.200mm lead.Stick.Brkt (x2)
1100551	WP Led Head, c/w Led's & Loom, Gland,Blk
AUM02870200001 CCPLED-18V625C-CKIT-HV	LED Power Pack, 18V 625mA, LP, HV (incl HIVE Node)
8003193	PCA: RF Node CT10678-A9 Int Antenna Horizontal

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

Isolux plot and value table for a 30m x 30m area serviced by a Weatherproof Supalite with each LED lamp head tilted down 30°, rolled out 30°. The Weatherproof Supalite mounted on the wall at a height of 3m and 6m (values in lux).

