

CLEVERTRONICS LP WEATHERPROOF SURFACE MOUNT WITH TWIN LIFELIGHT PRO PODS



PRODUCT INFORMATION

Part Number	CWP2LIFE-PRO-WPPOD-HV
MIC	AUT02820100001
Description	LP Premium LifeLight PRO, high performance, surface mounted IP65 Emergency with twin rotatable LED Pods
Construction	Polycarbonate
Mounting	Surface mount
Dimensions L x W x H	520mm x 180mm x 135mm
Weight	3.4kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 3200mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Twin Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.8 Watts (Standby), 5.5 Watts (Max)
IP Rating	IP65
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D160 C ₉₀ =D160

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550050	Battery, LP 3.2V 3200mAh 70mm lead, no Bracket
CLIFE-PRO-CKIT-NP	LifelightPro,Control Only,Batten,LP, NP
8003191	PCA: RF Node CT10678-A9 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.