



DYGC-CP-DS-RAOW

CleverEvac Dynamic Green Exit, Surface Mount, LP, Running Man Arrow One Way, Double Sided



Dynamic LEDs Sequencing Arrow

PRODUCT INFORMATION

Part Number	DYGC-CP-DS-RAOW
MIC	AUA02550410001
Description	CleverEvac Dynamic Green Exit, Surface Mount, LP, Running Man Arrow One Way, Double Sided
Construction	PC/ABS Body With PC Diffuser
Mounting	Ceiling Mounted, Double-sided
Dimensions L x W x H	367mm x 72mm x 214mm
Weight	2.0kg
Operating Mode	Maintained – Sequencing Inward Green LEDs Activated on VF/24V Input Trigger and Capable of Being Activated in Power-on and Battery-backed Mode. Dynamic GREEN Default Set to Activate Upon Mains Power Fail.
Testing System	Manual
Battery	Lithium Nanophosphate, 3.2V 3200mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Double-sided Pictograph, Two Elements (Running Man with Arrow)
Lamp(s)	LED Panel, 100,000 Hours
Operating Voltage	220-240V AC; 50Hz
Power Consumption	2.8W (Standby), 7.2W (Max)
Inrush Current (Max)	17.4A, 132µs
Earth Leakage	0.358mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =E2.5 C ₉₀ =C1.6
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550030	Battery
8002927	Driver Pack

Disclaimer: Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice, and suitable application of the products.