



## DYRC-UP-WM-R-HV

CLEVEREVAC DYNAMIC GREEN & RED X  
WALL MOUNT BLADE EXIT SIGN



### PRODUCT INFORMATION

Part Number	DYRC-UP-WM-R-HV
MIC	AUA02850380001
Description	LP Premium CleverEVAC Dynamic Green and Red X Blade EXIT sign, with Volt Free (VF) & 24V interface for ON/OFF activation of Dynamic Green & Red X Enhancement. <b>From 1<sup>st</sup> of April 2022 Dynamic GREEN default set to activate upon mains power fail.</b>
Construction	PC/ABS Body with PC Diffuser and Metal Enclosure
Mounting	Wall Surface Mount, Single-sided
Dimensions L x W x H	391mm x 90mm x 257mm
Weight	5.9 kg
Operating Mode	Maintained – Sequencing inward green LEDs or illuminated Red X with side flashing red LED's activated on VF/24V input trigger and capable of being activated in power-on and battery-backed mode. <b>From 1<sup>st</sup> of April 2022 Dynamic GREEN default set to activate upon mains power fail.</b>
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Iron Phosphate, 3.2V 6400mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Pictograph, Single element (Running Man)
Lamp(s)	LED panel, 100,000 hours
Operating Voltage	240V AC; 50Hz
Power Consumption	2.0 Watts (Standby), 9.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=E2.5 C90=E8
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1550250	BATT:LP 3.2V 6400mAh. SBS.
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

**Disclaimer:** Clevertronics Pty Ltd is a vendor of CleverEVAC products. It is not a fire engineer or designer. It does not purport to recommend its products for use in any particular application or to achieve any particular outcome. Purchasers and users of its products must take their own steps to ensure compliance with statutory requirements, safe practice and suitable application of the products.