



CLEVERTRONICS ECONOMY LITHIUM LED TUBE WIRE GUARD BATTEN



PRODUCT INFORMATION

Catalogue Number	EBS2L4S-WG-LI
Description	Economy Lithium 2x LED tube 4ft Wire Guard Batten with LED Emergency POD
Construction	Powder coated Steel body with PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	1274mm x 120mm x 110mm
Operating Mode	Sustained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Wire Guard
Lamp(s)	2x Philips Essential LEDtube T8, Col. 840, 30,000hours
Operating Voltage	240V AC; 50Hz
Total lumen output	3800 lm @ 95lm/W
Power Consumption	40 Watts (Lamp ON), 0.4 Watts (Standby)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT
3170080	LED TUBE 20W/840, 1.2m
ELIFE-X-LI-CKIT-NP	Lifelight, Control Only, 3.0Ah, No Plug

