



EBS4LEDS-LO-DIF-MS-HL-LI

CLEVERTRONICS ECONOMY LITHIUM ODYSSEY QUANTUM
LED DIFFUSED BATTEN – LOW POWER OUTPUT



PRODUCT INFORMATION

Part Number	EBS4LEDS-LO-DIF-MS-HL-LI
MIC	AUB03510100001
Description	Economy Lithium Odyssey Quantum 1200mm LED Diffused Batten with Hi/Lo Microwave Sensor Control of the Lamps (10%-100%), Low Power Output
Construction	Powder Coated Steel Body with Acrylic Prismatic Diffuser and PC/ABS End Caps
Mounting	Surface Mount
Dimensions L x W x H	1238mm x 120mm x 108mm
Weight	3.3 kg
Operating Mode	Sustained
Testing System	Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Diffuser	Acrylic Prismatic
Driver / Ballast	HL Driver – 55W, 500-1200mA, 12-50V
Lamp(s)	LED Strip Module, 4,000K Natural White, 50,000h Life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Power Consumption	20W (Lamps ON) 0.4W (Lamps OFF, Standby)
Total Lumen Output	2438lm @ 119lm/W
Operating Temperature	0°C to 40°C
IP Rating	IP20
AS2293 Classification	C0=D50 C90=D16
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560156	Battery
8002695	LED Strip (QTY 2)
1330070	Driver
1190118	Microwave Sensor
ELIFE-X-LI-CKIT-2LED-SL-NP	Driver Pack

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.