



CLEVERTRONICS ECONOMY LITHIUM 1200MM (4FT) NON-MAINTAINED BATTEN REPLACEMENT



PRODUCT INFORMATION

Catalogue Number	EBS4N-LI
Description	Economy Lithium 1200mm (4ft) non-maintained bare batten replacement utilising the Economy Lithium Lifelight
Construction	Powder coated Steel body and ABS/Polycarbonate End Caps
Mounting	Surface Mount
Dimensions L x W x H	1220mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	N/A - Manual test switch
Battery	Lithium Iron Phosphate, 3.2V 3000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x OSRAM OSRON MINT, High flux LED (Lifetime warranty on the Lamp head and loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 1.3 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1560150	BATT:LiFePO4 3.2V 3.0Ah 70mm lead,noBRKT
1100875	ELIFE-X-LI Head Assbly, Inc Adaptor Ring
ELIFE-X-LI-CKIT	Lifelight: LED, NM, Control Only, 3.0Ah

