



## EPIC-1500-LP-HV

Epic 1500mm Diffused Emergency Batten, LP, Switchable Colour, Zoneworks XT Hive



### PRODUCT INFORMATION

<b>Product Code</b>	EPIC-1500-LP-HV
<b>MIC</b>	AUB02810220001
<b>Description</b>	Epic 1500mm Diffused Emergency Batten, LP, Switchable Colour, Zoneworks XT Hive
<b>Switchable Colour CCT</b>	3000K / 4000K / 5700K (default 4000K)
<b>Construction</b>	Powder Coated Sheet Metal Base, Co-extruded IP40 PC Diffuser Assembly, PC End Caps
<b>Mounting</b>	Surface Mount
<b>Dimensions LxWxH (mm)</b>	1533x72x78
<b>Weight (kg)</b>	2.2
<b>Operating Mode</b>	Sustained
<b>Testing System</b>	Zoneworks XT HIVE (RF)
<b>Battery</b>	Lithium Iron Phosphate, 3.2V 6400mAh
<b>Charging Method</b>	Intelligent current limited constant voltage
<b>Diffuser</b>	Co-extruded IP40 PC Diffuser Assembly
<b>Driver / Ballast</b>	LC 57W, 700-1050mA, flexC Ip SNC4
<b>Lamp(s)*</b>	Dual LED strip module, 3000K warm white, 5700K cool white, >50,000hr life, Ra>80 L70/B50 Ta 40°C; Reported >54,000hr, Projected 158,000hr L80/B50 Ta 40°C; Reported >54,000hr, Projected 99,000hr
<b>Supply Voltage</b>	220-240V~ 50Hz
<b>Power Factor</b>	0.90 @ High Output
<b>Supply Current</b>	180mA +/- 20mA
<b>Inrush Current (Max)</b>	TBA
<b>Earth Leakage</b>	0.427mA
<b>Total lumen output</b>	6117 lm (133 lm/W) @ default 4000K, standby lamp on (refer to table below for details)
<b>Power Consumption</b>	46.03W @ default 4000K High Output, standby, lamp on (refer to table below for details)
<b>Operating Temperature</b>	1°C to 40°C
<b>IP Rating</b>	IP20
<b>Impact Rating</b>	IK03
<b>AS2293 Classification</b>	C0=D63, C90=D40
<b>LED MacAdam Step (SDCM)</b>	4
<b>Applicable Standards</b>	AS/NZS3820, CISPR15, AS/NZS2293.3
<b>Compliance Marking (RCM)</b>	



## EPIC-1500-LP-HV

Epic 1500mm Diffused Emergency Batten, LP, Switchable Colour, Zoneworks XT Hive



### REPLACEMENT PARTS

COMPONENT	PART NUMBER & DESCRIPTION
1550230	Battery
1330069	LED Driver
8050571	LED Strip
AUM02870110002 CLIFE-PRO-CKIT-HV-NP	Emergency Driver
8003191	HIVE Node

Power Consumption & Lumen Output	Max Charge, Lamp On	Standby Charge, Lamp On	Standby Charge, Lamp Off	Lumen Output
3000K	50.45W	48.15W	0.7W	5555 lm
4000K (DEFAULT)	48.33W	46.03W	0.7W	6117 lm
5700K	50.49W	48.19W	0.7W	5883 lm

\*The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order