



EPIC-1500

Epic 1500mm Diffused Batten, Switchable Colour & Output



PRODUCT INFORMATION	
Product Code	EPIC-1500
MIC	AUB04610220001
Description	Epic 1500mm Diffused Batten, Switchable Colour
Switchable Colour CCT	3000K / 4000K / 5700K (default 4000K)
Construction	Powder Coated Sheet Metal Base, Co-extruded IP40 PC Diffuser Assembly, PC End Caps
Mounting	Surface Mount
Dimensions LxWxH (mm)	1533x72x78
Weight (kg)	2.2
Diffuser	Co-extruded IP40 PC Diffuser Assembly
Driver / Ballast	LC 57W, 700-1050mA, flexC Ip SNC4
Lamp(s)*	Dual LED strip module, 3000K warm white, 5700K cool white, >50,000hr life, Ra>80 L70/B50 Ta 40°C; Reported >54,000hr, Projected 158,000hr L80/B50 Ta 40°C; Reported >54,000hr, Projected 99,000hr
Supply Voltage	220-240V~ 50Hz
Power Factor	0.90 @ High Output
Supply Current	180mA +/- 20mA
Inrush Current (Max)	28.4A, <88µs
Earth Leakage	0.152mA
Total lumen output	6117 lm (134.9 lm/W) @ default 4000K, (refer to table below for details)
Power Consumption	45.33W
Operating Temperature	1°C to 40°C
IP Rating	IP20
Impact Rating	IK03
LED MacAdam Step (SDCM)	4
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	



EPIC-1500

Epic 1500mm Diffused Batten, Switchable Colour & Output



REPLACEMENT PARTS

COMPONENT	PART NUMBER & DESCRIPTION
1330069	LED Driver
8050571	LED

Power Consumption & Lumen Output	Lamp On	Lumen Output
3000K	47.45W	5555 lm
4000K (DEFAULT)	45.33W	6117 lm
5700K	47.49W	5883 lm

*The projected value has been calculated by extrapolation of the LM80 data using the Energy Star Calculator

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order