



## FBKLED-BLK

Bunkalite IP65 Weatherproof Circular,  
Non-emergency, Black



### PRODUCT INFORMATION

Part Number	FBKLED-BLK
MIC	AUS04620380001
Description	Bunkalite IP65 Weatherproof Circular, Non-Emergency, Black
Construction	Base Material: Die-cast Aluminium Diffuser Cover Material: Opal Polycarbonate
Mounting	Surface Mount
Dimensions	Ø 360mm x 145mm
Weight	4.5kg
Diffuser	Polycarbonate
Driver	Constant current, 480mA, 50,000hrs
Lamp(s)	LED module, 4,000K natural white, 50,000h life, Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.9
Total Lumen Output	1900lm @ 137lm/W
Power Consumption	13.9 Watts
IP Rating	IP65
IK Rating	IK10
Operating Temperature	0°C to 40°C
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1331102-B	240V Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order