

CLEVERTRONICS L10 600MM (2FT) NON-MAINTAINED BATTEN REPLACEMENT (ZONWORKS XT HIVE)



PRODUCT INFORMATION

Catalogue Number	LBS2N-HV
MIC	AUB01810030001
Description	L10 Optimum 600mm (2ft) Non-Maintained Bare Batten Replacement utilising the Lifelight - High Performance Emergency Light
Construction	Powder coated Steel body and ABS/Polycarbonate End Caps
Mounting	Surface mount
Dimensions L x W x H	611mm x 111mm x 54mm
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	4.5W (MAX Charge - Lamp ON), 1.3W (Standby Lamp OFF)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D40 C ₉₀ =D40

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, Brkt
1100925	LifeLight Head Assembly, Round, LT, 1LED
AUM01870160101 LLIFE-CKIT-HVEXTA-NP	Lifelight: LED, Control Only, L10, HV external, NP (incl Hive node)
8003195	PCA: RF Node CT10678-A7 Ext Antenna

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order