



CLEVERTRONICS L10 1200MM (4FT) NON-MAINTAINED BATTEN REPLACEMENT (DALI)



PRODUCT INFORMATION

Catalogue Number	LBS4N-DALI
Description	L10 Optimum 1200mm (4ft) Non-Maintained Bare Batten Replacement Utilising the Lifelight - High Performance, Emergency Light with Premium Lithium Battery Technology
Construction	Powder coated Steel body and ABS/Polycarbonate End Caps
Mounting	Surface Mount
Dimensions L x W x H	1220mm x 110mm x 50mm
Operating Mode	Non-maintained
Testing System	DALI compatible
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 2.2 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
1100830	Lifelight Pro Head Assembly, Round
LLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP/L10
8002200	PCA:DALI Node, #CT10410-A3

DALI EM

L10 LITHIUM NANOPHOSPHATE®

OPTIMUM

NOTHING ELSE COMPETES WITH NANOPHOSPHATE®