



## LCFLED-HV-BLK

CLEVERTRONICS L10 CLEVERFIT EXIT, BLACK



### PRODUCT INFORMATION

Part Number	LCFLED-HV-BLK
MIC	AUA01810100002
Description	L10 Premium Cleverfit Emergency Exit
Construction	ABS body and diffuser with polycarbonate clear tamper proof cover
Mounting	Wall, ceiling single sided and & ceiling double sided
Dimensions L x W x H	355mm x 80mm x 215mm
Weight	1.8kg
Operating Mode	Maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED, 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby) 4 Watts (Max)
Inrush Current (Max)	51A/22us
Earth Leakage	0.333mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D6.3, C90=D5
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530050	Battery
8002710	Emergency LED Panel
8002358	Emergency Driver
8003191	Emergency Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.