



LJWELED-WM-FZR-40-R

CLEVERTRONICS L10 WEATHERPROOF JUMBO EXIT WALL MOUNT FOR LOW TEMPERATURE APPLICATIONS



PRODUCT INFORMATION

Part Number	LJWELED-WM-FZR-40-R
MIC	AUA01320170001
Description	L10 Optimum Wall Mounted Weatherproof Jumbo Emergency EXIT for Low Temperature Applications
Construction	Polycarbonate Clear Cover, Polycarbonate Base
Mounting	Wall mount, Single-sided
Dimensions L x W x H	560mm x 280mm x 130mm
Weight	5.5kg
Operating Mode	Maintained
Testing System	Manual testing
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	Running Man (must specify diffuser combination)
Lamp(s)	4 x (6 high intensity, low energy LED) surface mounted onto a replaceable Lamp Bar - 100,000hrs
Operating Voltage	240V AC; 50Hz
Power Consumption	2.8 Watts (Standby), 5.3 Watts (Max)
IP Rating	IP66/IP67
Operating Temperature	-25°C to 40°C
AS2293 Classification	C0=E1.6 C90=C1.25
Impact Rating	IK08 (side surface) IK09 (front surface)
Viewing Distance	40m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead, Brkt
AUM01370270001 LJWELED-FZR-40-CKIT	WP LED Exit, Control Kit, FZR, L10
8002122	PCA:Duris E5 LED Strip 5LED ,CT10152-D4

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order